



ALDANMARK
CONSULTING ENGINEERS

STORMWATER REPORT

Unit Development
12 Fenwick Crescent
Derwent Park TAS 7009

260414 SR 25 E 52 - 47 Rev B

Lower Ground
199 Macquarie Street
Hobart TAS 7000

GPO Box 1248
Hobart TAS 7001

03 6234 8666

mail@aldanmark.com.au
www.aldanmark.com.au

ABN 79 097 438 714

**GLENORCHY CITY COUNCIL
PLANNING SERVICES**

APPLICATION No. : PLN-26-025

DATE RECEIVED: 17 April 2026

14/04/2026

PROJECT INFORMATION

DOCUMENT TITLE	Stormwater Report - 25 E 52 - 47 Rev B
PROJECT LOCATION	12 Fenwick Crescent, Derwent Park TAS 7009
CLIENT ORGANISATION	Lyden Builders
CLIENT REFERENCE	Unit Development
CLIENT CONTACT/S	
ALDANMARK REFERENCE	25 E 52 - 47
ALDANMARK CONTACT/S	Giancarlo Rigoli (grigoli@vertotas.com.au)

Copyright © Aldanmark Pty Ltd 2022. All rights reserved. No part of this report may be reproduced or distributed in any form or by any means, or stored in a database or retrieval system without the prior written permission of Aldanmark Pty Ltd. This document is confidential and contains privileged information. This information is not to be given to or discussed with anyone other than to those that are privileged to view the information.

DOCUMENT CONTROL

REVISION	DATE	REVISION DETAILS	PREPARED	VERIFIED	APPROVED
A	23/03/2026	Development Approval	GR		DE
B	14/04/2026	Development Approval	GR		DE

**GLENORCHY CITY COUNCIL
PLANNING SERVICES**

APPLICATION No. : PLN-26-025

DATE RECEIVED: 17 April 2026

14/04/2026

TABLE OF CONTENTS

TABLE OF FIGURES	4
1. INTRODUCTION	5
2. SITE OVERVIEW.....	5
3. CATCHMENT MODEL.....	6
3.1 MODELLING APPROACH.....	6
3.2 DESIGN RAINFALL DEPTHS	6
3.3 STORM LOSSES.....	6
3.4 SITE CATCHMENTS	7
3.5 PROPOSED DEVELOPMENT PEAK OUTFLOWS	7
4. MODEL RESULTS	7
4.1 PEAK FLOWS.....	7
4.2 ONSITE DETENTION.....	8
4.3 ONSITE DETENTION OUTFLOW	8
5. CONCLUSION	8
6. APPENDIX A.....	9
6.1 SITE CATCHMENT PLAN	9
6.2 DRAINS MODEL	9
7. APPENDIX B – BOX AND WHISKER PLOTS.....	10
7.1 PRE DEVELOPMENT.....	10
7.2 POST DEVELOPMENT	10

**GLENORCHY CITY COUNCIL
PLANNING SERVICES**

APPLICATION No. : PLN-26-025

DATE RECEIVED: 17 April 2026

14/04/2026

TABLE OF FIGURES

FIGURE 1: LOCALITY PLAN	5
FIGURE 2: SITE CATCHMENT PLAN	9
FIGURE 3: DRAINS MODEL.....	9
FIGURE 4: PRE-DEVELOPMENT 5% AEP OUTFLOW	10
FIGURE 5: POST-DEVELOPMENT 5% AEP OUTFLOW - UNMITIGATED.....	10
FIGURE 6: POST-DEVELOPMENT 5% AEP OUTFLOW - MITIGATED.....	11



**GLENORCHY CITY COUNCIL
PLANNING SERVICES**
APPLICATION No. : PLN-26-025
DATE RECEIVED: 17 April 2026

14/04/2026

1. INTRODUCTION

Verto have been engaged to provide a stormwater report for the proposed development at 12 Fenwick Crescent, Derwent Park.

The development must comply with the stormwater quantity requirements of the Glenorchy City Council Stormwater Management Policy and Planning RFI PLN-26-025 dated 3rd of March 2026:

- Stormwater runoff from the site will be no greater than pre-existing runoff for a 5% AEP rainfall event.
- The stormwater system must incorporate water sensitive urban design principles for the treatment and disposal of stormwater.

This report aims to demonstrate that the development at 12 Fenwick Crescent, Derwent Park complies with the above stormwater quality and quantity requirements.

2. SITE OVERVIEW

The subject site is currently undeveloped with grass and minimal vegetation as shown in Figure 1. No known stormwater lot connection has been located however a stormwater and sewer easement runs along the rear of the property.

Two residential units are proposed to be constructed on the subject site, as well as new concrete driveway and parking areas as. The increase in impervious area within the site is expected to increase the quantity of site stormwater runoff.




FIGURE 1: LOCALITY PLAN

**GLENORCHY CITY COUNCIL
PLANNING SERVICES**

APPLICATION No. : PLN-26-025

DATE RECEIVED: 17 April 2026

14/04/2026

3. CATCHMENT MODEL

3.1 MODELLING APPROACH

DRAINS software was utilised to calculate the site runoff and to determine the size of the site’s stormwater conveyance and detention infrastructure. A screen shot of the DRAINS model can be found in Appendix 6.2.

The Initial Loss / Continuing Loss (IL-CL) loss model was applied within DRAINS. The parameters for the loss model were retrieved from the ARR Data Hub website (<https://data.arr-software.org/>).

3.2 DESIGN RAINFALL DEPTHS

Rainfall depths for the model were retrieved from the Bureau of Meteorology website (<http://www.bom.gov.au/water/designRainfalls/revised-ifd/>). Temporal patterns, pre-burst rainfall depths and rural losses were sourced from the ARR Data Hub website.

TABLE 2: IFD DESIGN RAINFALL DEPTHS

Duration (minutes)	5% AEP (mm/hr)	2% AEP (mm/hr)	1% AEP (mm/hr)
1	138.6	169.2	194.4
5	84.84	102.36	116.4
10	63.6	78.6	91.2
20	44.1	54.3	63
25	38.88	47.52	54.72
30	34.8	42.4	48.8
45	27.07	36.7	37.2
60	22.7	27.1	30.7
90	17.8	21	25.53
120	15.05	17.65	19.65

3.3 STORM LOSSES

Rural initial and continuing losses were sourced from the ARR Data Hub website. Impervious area losses have been set as per advice in ARR 2019 Book 5 Chapter 3 Section 3.5.3.1.2. Table 3.3 shows the storm losses assumed in the DRAINS model.

TABLE 3: ASSUMED STORM LOSSES (ARR)

	Without Climate Change
Impervious Area Initial Losses (mm)	1
Impervious Area Continuing Losses (mm/hr)	0
Pervious Area Initial Losses (mm)	28
Pervious Area Continuing Losses (mm/hr)	3.7

14/04/2026

3.4 SITE CATCHMENTS

The site catchments assumed for the initial loss – continuous loss calculations were determined from the architectural site plan prepared by Pinnacle dated February 2026. Table 4 below outlines the proportions of the effective impervious area (EIA), remaining impervious area (RIA) and pervious area (PA). The pre-development catchment was simulated as a single homogenous catchment. In the post-development scenarios, separate catchments were defined for each inlet pit, each unit roof area, and for the remaining area bypassing the site drainage system. Refer to Appendix 6.1 for the site catchment plan.

Times of concentration for all catchments were determined within DRAINS using the kinematic wave equation.

TABLE 4: SITE CATCHMENT BREAKDOWN

CATCHMENT	AREA (m ²)	AREA (ha)	EIA (%)	RIA (%)	PA (%)
Pre-development	770	0.077	55	0	45
Post -development	770	0.077	60	4	36

3.5 PROPOSED DEVELOPMENT PEAK OUTFLOWS

As per the Glenorchy City Councils Stormwater Management Policy, a factor of 0.55 (55%) with the remaining area being pervious was applied to the pre-development catchment to obtain the outflow. As per the Glenorchy City Council RFI dated 30th March 2026, a time of concentration (Tc) of 30 minutes is to be analysed for the site. As shown below in Table 5, the pre-development site runoff is 4 L/s.

TABLE 5: UNMITIGATED SITE RUNOFF

5% AEP	SITE RUNOFF (L/S)	CRITICAL 5% AEP STORM DURATION (MINS)
Site Discharge		
Pre-development	4	30
Post-development (Unmitigated)	10	5

4. MODEL RESULTS

4.1 PEAK FLOWS

The results from the DRAINS Analysis model show that the post-development site runoff 12 Fenwick Crescent, Derwent Park is increased by 6 l/s over pre-existing runoff quantities for a 5% AEP storm event as shown in Table 5. As per Glenorchy City Council’s Planning RFI point 8, on site detention is required to reduce the post development peak runoff below the pre-development runoff.

Refer to Appendix 7 for box and whisker plots of pre & post development outflows.

14/04/2026

4.2 ONSITE DETENTION

To reduce the post-development site outflow below pre-development quantities, an on-site detention system was modelled in DRAINS. The results of the model show that an end of line pit fitted with a 50mm orifice plate is required to reduce the post – development outflow to match the pre – development outflow.

4.3 ONSITE DETENTION OUTFLOW

TABLE 1: DETENTION MODEL SUMMARY - 5% AEP

5 % AEP	SITE RUNOFF (L/S)	CRITICAL STORM DURATION (MINS)
Site Discharge		
Pre-development	4	30
Post-development (Unmitigated)	10	5
Post-development with OSD	4	20

5. CONCLUSION

This report has demonstrated that the proposed development at 12 Fenwick Crescent, Derwent Park complies with the stormwater quantity conditions of Glenorchy City Council’s planning RFI and Stormwater Management Policy.

Note:

- No assessment has been undertaken of Council’s stormwater infrastructure and its capacity.
- This report assumes the Council stormwater main has capacity for the pre-development peak discharge.
- It is the responsibility of Council to assess their infrastructure and determine the impact (if any) of altered inflows into their stormwater network.

Please contact me at grigoli@vertotas.com.au if you require any additional information.

Yours faithfully,



Giancarlo Rigoli
Graduate Civil / Structural Engineer

14/04/2026

6. APPENDIX A

6.1 SITE CATCHMENT PLAN




FIGURE 2: SITE CATCHMENT PLAN

6.2 DRAINS MODEL




FIGURE 3: DRAINS MODEL

14/04/2026

7. APPENDIX B – BOX AND WHISKER PLOTS

7.1 PRE DEVELOPMENT




FIGURE 4: PRE-DEVELOPMENT 5% AEP OUTFLOW

7.2 POST DEVELOPMENT




FIGURE 5: POST-DEVELOPMENT 5% AEP OUTFLOW - UNMITIGATED

14/04/2026




FIGURE 6: POST-DEVELOPMENT 5% AEP OUTFLOW - MITIGATED